

## T TOP CONSOLE COVER

**1. POSITION YOUR COVER:** Position the cover so the zipper will be on the starboard side of the console. At the top of the zipper there will be a 24" strap with quick release buckle this will secure the cover the T-Top structure on your boat. The port side of the cover also has a 24" strap sewn to it to secure the port side in the same fashion.



**2. ADJUST THE LENGTH OF THE COVER:** Once the cover has been attached and zipped around the console and helm seat then adjust the 24" straps until the cover just reaches the floor of the boat.

**3. TIGHTEN THE BACK STRAPS:** The cover comes with (3) 48" straps that cross the back panel of the cover behind and on top of the helm seat. These need to be adjusted to allow some of the slack to be pulled behind the helm seat. Start with the lowest one and tighten to improve the fit.



**4. SECURE THE WEATHER FLAP:** Now that the straps are in place you can secure the weather flap that is sewn to the front panel over the windshield bar and across the top of the console. This panel will fasten to the buckles attached to the outside of the cover over the helm seat, adjust these straps to allow this flap to cover the opening over the console.



**5. REMOVAL AND REHANG:** To remove simply unbuckle the quick release buckles on the weather flap. Then unzip the side zipper. Unbuckle the strap going up the T Top structure on the zipper side. Then unbuckle the strap going to the T Top structure on the port side. There is no need to release the other straps on the cover. Simply fold and store the cover as needed. To re hang simply reverse this step. There should be no need to readjust any straps as they were set on the initial installation.

Westland Industries  
15 Quality Circle  
Vonore, Tn. 37885

1-800-835-7992



www.westlandcovers.com