

<b>1968</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
17	17' - 0"	7' - 2"	7"	X	20"	1050 lbs	24 Gal.	X	115
Perdue 18	18' - 6"	7' - 9"	8"	X	20"	1250 lbs	24 Gal.	X	115
19	18' - 7"	8' - 0"	8"	X	20"	1400 lbs	32 Gal.	X	150
22	21' 9"	8' - 0"	10"	X	20"	1800 lbs	44 Gal.	X	225
25 Inboard	24' - 8"	10' - 0"	21"	X	Full	4000 lbs	104 Gal.	X	X
<b>1969</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
17	17' - 0"	7' - 2"	7"	X	20"	1050 lbs	24 Gal.	X	115
19	18' - 7"	8' - 0"	10"	X	20"	1400 lbs	32 Gal.	X	150
22	21' - 9"	8' - 0"	10"	X	20"	1800 lbs	44 Gal.	X	225
<b>1970</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
17	17' - 0"	7' - 2"	7"	X	20"	1050 lbs	24 Gal.	X	135
19	18' - 7"	8' - 0"	8"	X	20"	1400 lbs	32 Gal.	X	150
22	21' - 9"	8' - 0"	10"	X	20"	1800 lbs	51 Gal.	X	230
23	23' - 0"	8' - 0"	10"	X	20"	2550 lbs	70 Gal.	X	250
23 Inboard	23' - 0"	8' - 0"	22"	X	Full	3600 lbs	75 Gal.	X	X
231 Cabin I/O	23' - 0"	8' - 0"	12"	X	Full	3800 lbs	70 Gal.	X	X
232 Cabin I/O	23' - 0"	8' - 0"	12"	X	Full	3650 lbs	70 Gal.	X	X
<b>1971</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
17	17' - 0"	7' - 2"	7"	X	20"	1050 lbs	24 Gal.	X	135
19	18' - 7"	8' - 0"	8"	X	20"	1400 lbs	32 Gal.	X	150
20	20' - 0"	8' - 0"	9"	X	20"	1600 lbs	44 Gal.	X	200
22	21' - 9"	8' - 0"	10"	X	20"	1800 lbs	51 Gal.	X	230
23 Inboard	23' - 0"	8' - 0"	22"	X	Full	3600 lbs	75 Gal.	X	X
231 Cabin I/O	23' - 0"	8' - 0"	12"	X	Full	3800 lbs	70 Gal.	X	X
232 Cabin I/O	23' - 0"	8' - 0"	12"	X	Full	3650 lbs	70 Gal.	X	X
<b>1972</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
17 Standard	17' - 0"	7' - 2"	7"	X	20"	1050 lbs	24 Gal.	X	135
17 Angler	17' - 0"	7' - 2"	7"	X	20"	1050 lbs	24 Gal.	X	135
19	18' - 7"	7' - 2"	8"	X	20"	1400 lbs	32 Gal.	X	150
20	20' - 0"	8' - 0"	9"	X	20"	1600 lbs	44 Gal.	X	200

22	21' - 9"	8' - 0"	10"	X	20"	1800 lbs	51 Gal.	X	230
23	23' - 0"	8' - 0"	10"	X	20"	2550 lbs	70 Gal.	X	250
23 Cabin I/O	23' - 0"	8' - 0"	12"	X	Full	3800 lbs	70 Gal.	X	X
23 Open I/O	23' - 0"	8' - 0"	12"	X	Full	36560 lbs	70 Gal.	v	X
<b>1973</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
17 Standard	17' - 0"	7' - 2"	7"	12°	20"	1050 lbs	24 Gal.	X	135
17 Angler	17' - 0"	7' - 2"	7"	12°	20"	1050 lbs	24 Gal.	X	135
19	18' - 7"	7' - 2"	8"	X	20"	1400 lbs	32 Gal.	X	150
20	20' - 0"	8' - 0"	9"	19°	20"	1600 lbs	44 Gal.	X	200
22	21' - 9"	8' - 0"	10"	X	20"	1800 lbs	51 Gal.	X	230
23	23' - 0"	8' - 0"	10"	X	20"	2550 lbs	70 Gal.	X	250
23 Cabin I/O	23' - 0"	8' - 0"	12"	X	Full	3800 lbs	70 Gal.	X	X
23 Open I/O	23' - 0"	8' - 0"	12"	X	Full	3650 lbs	70 Gal.	X	X
<b>1974</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
15	15' - 0"	6' - 2"	6"	X	20"	850 lbs	X	X	70
17 Standard	17' - 0"	7' - 2"	7"	X	20"	1050 lbs	24 Gal.	X	135
17 Angler	17' - 0"	7' - 2"	7"	X	20"	1050 lbs	24 Gal.	X	135
19B	18' - 7"	8' - 0"	8"	X	20"	1400 lbs	32 Gal.	X	150
20	20' - 0"	8' - 0"	9"	X	20"	1600 lbs	44 Gal.	X	200
22B	21' - 9"	8' - 0"	10"	X	20"	1800 lbs	51 Gal.	X	230
23	23' - 0"	8' - 0"	10"	X	20"	2550 lbs	70 Gal.	X	250
23 Cabin I/O	23' - 0"	8' - 0"	12"	X	Full	3800 lbs	70 Gal.	X	X
23 Open I/O	23' - 0"	8' - 0"	12"	X	Full	3650 lbs	70 Gal.	X	X
<b>1975</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
15	15' - 0"	6' - 2"	6"	X	20"	850 lbs	X	X	70
17 Standard	17' - 0"	7' - 2"	7"	X	20"	1050 lbs	24 Gal.	X	135
17 Angler	17' - 0"	7' - 2"	7"	X	20"	1050 lbs	24 Gal.	X	135
19B	18' - 7"	8' - 0"	8"	X	20"	1400 lbs	32 Gal.	X	150
20	20' - 0"	8' - 0"	9"	X	20"	1600 lbs	44 Gal.	X	200
22B	21' - 9"	8' - 0"	10"	X	20"	1800 lbs	51 Gal.	X	230
23	23' - 0"	8' - 0"	10"	X	20"	2550 lbs	70 Gal.	X	250
23 Cabin I/O	23' - 0"	8' - 0"	12"	X	Full	3800 lbs	70 Gal.	X	X

23 Open I/O	23'-0"	8'- 0"	12"	X	Full	3650 lbs	70 Gal.	X	X
23 Inboard	23'-0"	8'- 0"	22"	X	Full	3600 lbs	74 Gal.	X	260
26 Inboard	26'-0"	9'- 6"	22"	X	Full	6500 lbs	110 Gal.	X	X
<b>1976</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
171 Classic	17'- 0"	7'- 2"	7"	X	20"	1400 lbs	24 Gal.	X	135
171 Angler	17'-0"	7'-2"	7"	X	20"	1200 lbs	24 Gal.	X	135
19B	18'-7"	8'- 0"	8"	X	20"	1525 lbs	32 Gal.	X	150
20	20'-0"	8'- 0"	9"	X	20"	1775 lbs	44 Gal.	X	200
22B	21'-9"	8'- 0"	10"	X	20"	1950 lbs	51 Gal.	X	230
23	23'-0"	8'- 0"	10"	X	25"	2500 lbs	70 Gal.	X	250
23 Cabin I/O	23'-0"	8'- 0"	12"	X	Full	3650 lbs	70 Gal.	X	X
23 OpenI/O	23'-0"	8'- 0"	12"	X	Full	3650 lbs	70 Gal.	X	X
23 Inboard	23'-0"	8'- 0"	22"	X	Full	3600 lbs	74 Gal.	X	260
25	25'-7"	8'- 0"	14"	X	25"	2900 lbs	120 Gal.	X	300
26 Inboard	26'-0"	9'- 6"	22"	X	Full	6500 lbs	110 Gal.	X	X
<b>1977</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
15	15'- 0"	6'- 2"	6"	X	20"	875 lbs	X	X	70
17 Standard	17'-0"	7'-2"	7"	X	20"	1400 lbs	24 Gal.	X	135
17 Angler	17'-0"	7'- 2"	7"	X	20"	1200 lbs	24 Gal.	X	135
19B	18'-7"	8'- 0"	8"	X	20"	1525 lbs	32 Gal.	X	150
20	20'-0"	8'- 0"	9"	X	20"	1775 lbs	44 Gal.	X	200
21	21'-0"	8'- 0"	12"	X	25"	2100 lbs	86 Gal.	X	200
22B	21'-9"	8'- 0"	10"	X	20"	2000 lbs	51 Gal.	X	230
23	23'-0"	8'- 0"	10"	X	25"	2500 lbs	86 Gal.	X	250
23 Inboard	23'-0"	8'- 0"	24"	X	Full	3800 lbs	80 Gal.	X	260
25	25'-7"	8'- 0"	14"	X	25"	2700 lbs	86 Gal.	X	300
26 Inboard	26'-0"	9'- 6"	22"	X	Full	6500 lbs	110 Gal.	X	X
<b>1978</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
17 Standard	17'- 0"	7'- 2"	7"	X	20"	1400 lbs	24 Gal.	X	135
17 Angler	17'-0"	7'-2"	7"	X	20"	1200 lbs	24 Gal.	X	135
19B	18'-7"	8'- 0"	8"	X	20"	1525 lbs	32 Gal.	X	150
20	20'-0"	8'- 0"	9"	X	20"	1775 lbs	44 Gal.	X	200

21	21'-0"	8'- 0"	12"	X	25"	2100 lbs	86 Gal.	X	230
23	23'-0"	8'- 0"	10"	X	25"	2500 lbs	86 Gal.	X	250
23 Inboard	23'-0"	8'- 0"	24"	X	Full	3800 lbs	80 Gal.	X	260
25	25'-7"	8'- 0"	14"	X	25"	2700 lbs	86 Gal.	X	300

<b>1979</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
17 Standard	17'- 0"	7'- 2"	7"	X	20"	1400 lbs	24 Gal.	X	135
17 Angler	17'-0"	7'-2"	7"	X	20"	1200 lbs	24 Gal.	X	135
19B	18'-7"	8'- 0"	8"	X	20"	1525 lbs	32 Gal.	X	150
20	20'-0"	8'- 0"	9"	X	20"	1775 lbs	44 Gal.	X	200
21	21'-0"	8'- 0"	12"	X	25"	2100 lbs	86 Gal.	X	230
23	23'-0"	8'- 0"	10"	X	25"	2500 lbs	86 Gal.	X	250
23 Inboard	23'-0"	8'- 0"	24"	X	Full	3800 lbs	80 Gal.	X	260
25	25'-7"	8'- 0"	14"	X	25"	2700 lbs	86 Gal.	X	300

<b>1980</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
17 Standard	17' - 0"	7' - 2"	7"	12°	20"	1400 lbs	24 Gal.	X	135
17 Angler	17' - 0"	7' - 2"	7"	12°	20"	1200 lbs	24 Gal.	X	135
18	18' - 2"	6' - 7"	6"	X	20"	1150 lbs	30 Gal.	X	140
20B	20' - 0"	8' - 0"	9"	19°	20"	1775 lbs	60 Gal.	X	200
21	21' - 0"	8' - 0"	12"	19°	25"	2100 lbs	86 Gal.	X	230
224	22' - 7"	8' - 0"	14"	19°	25"	2200 lbs	112 Gal.	X	250
228 Cuddy	22' - 7"	8' - 0"	14"	19°	25"	2300 lbs	122 Gal.	X	250
235	23' - 0"	8' - 0"	10"	19°	25"/30"	2500 lbs	122 Gal.	X	250
236 Inboard	23' - 0"	8' - 0"	24"	16°	Full	3800 lbs	80 Gal.	X	260
238 Walk Around	23' - 0"	8' - 6"	14"	X	25"	2500 lbs	121 Gal.	X	250
25	25' - 7"	8' - 0"	14"	23°	25"	2800 lbs	151 Gal.	X	300
258 Cuddy	25' - 6"	8' - 0"	18"	23°	25"	3200 lbs	151 Gal.	X	300

<b>1981</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
17 Standard	17'- 0"	7'- 2"	7"	12°	20"	1400 lbs	35 Gal.	X	135
17 Angler	17'-0"	7'-2"	7"	12°	20"	1200 lbs	35 Gal.	X	135
20B	20'-0"	8'- 0"	9"	19°	20"	1775 lbs	60 Gal.	X	200
21	21'-3"	8'- 0"	12"	19°	25"	2100 lbs	86 Gal.	X	230
224	22'-7"	8'- 0"	14"	19°	25"	2200 lbs	112 Gal.	X	250

228 Cuddy	22'-7"	8'- 0"	14"	19°	25"	2300 lbs	122 Gal.	X	250
235	23'-0"	8'- 0"	10"	19°	25"/30"	2500 lbs	122 Gal.	X	250
236 Inboard	23'-0"	8'- 0"	24"	16°	Full	3800 lbs	80 Gal.	X	260
238 Walk Around	23'-0"	8'- 6"	14"	X	25"	2500 lbs	121 Gal.	X	250
25	25'-7"	8'- 0"	14"	23°	25"	2800 lbs	151 Gal.	X	300
258 Cuddy	25'-6"	8'- 0"	18"	23°	25"	3200 lbs	151 Gal.	X	300

<b>1982</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
17 Standard	17'- 0"	7'- 2"	7"	12°	20"	1400 lbs	35 Gal.	X	135
17 Angler	17'-0"	7'-2"	7"	12°	20"	1200 lbs	35 Gal.	X	135
20B	20'-0"	8'- 0"	9"	19°	20"	1775 lbs	60 Gal.	X	200
21	21'-3"	8'- 0"	12"	19°	25"	2100 lbs	86 Gal.	X	230
224	22'-7"	8'- 0"	14"	19°	25"	2200 lbs	112 Gal.	X	250
228 Cuddy	22'-7"	8'- 0"	14"	19°	25"	2300 lbs	122 Gal.	X	250
235	23'-0"	8'- 0"	10"	19°	25"/30"	2500 lbs	122 Gal.	X	250
236 Inboard	23'-0"	8'- 0"	24"	16°	Full	3800 lbs	80 Gal.	X	260
238 Walk Around	23'-0"	8'- 6"	14"	X	25"	2500 lbs	121 Gal.	X	250
25	25'-7"	8'- 0"	14"	23°	25"	2800 lbs	151 Gal.	X	300
258 Cuddy	25'-6"	8'- 0"	18"	23°	25"	3200 lbs	151 Gal.	X	300

<b>1983</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
17 Standard	17'- 0"	7'- 2"	7"	12°	20"	1400 lbs	35 Gal.	X	135
17 Angler	17'-0"	7'-2"	7"	12°	20"	1200 lbs	35 Gal.	X	135
18	18'-2"	6'-7"	6"	X	20"	1150 lbs	30 Gal.	X	140
20B	20'-0"	8'- 0"	9"	19°	20"	1775 lbs	60 Gal.	X	200
21	21'-3"	8'- 0"	12"	19°	25"	2100 lbs	86 Gal.	X	230
224	22'-7"	8'- 0"	14"	19°	25"	2200 lbs	112 Gal.	X	250
228 Cuddy	22'-7"	8'- 0"	14"	19°	25"	2300 lbs	122 Gal.	X	250
235	23'-0"	8'- 0"	10"	19°	25"/30"	2500 lbs	122 Gal.	X	250
236 Inboard	23'-0"	8'- 0"	24"	16°	Full	3800 lbs	80 Gal.	X	260
238 Walkaround	23'-0"	8'- 6"	14"	X	25"	2500 lbs	121 Gal.	X	250
25	25'-7"	8'- 0"	14"	23°	25"	2800 lbs	151 Gal.	X	300
258 Cuddy	25'-6"	8'- 0"	18"	23°	25"	3200 lbs	151 Gal.	X	300

<b>1984</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
-------------	-------------------	------	------------	---------------------	----------------	---------------	---------------	----------------------	--------

172 Standard	17'- 0"	7'- 2"	7"	12°	20"	1400 lbs	35 Gal.	X	135
171 Angler	17'-0"	7'-2"	7"	12°	20"	1200 lbs	35 Gal.	X	135
20C	20'-0"	8'-0"	9"	19°	20"	1775 lbs	60 Gal.	X	200
21B	21'-7"	8'- 0"	12"	19°	25"	2100 lbs	86 Gal.	X	235
224	22'-7"	8'- 0"	14"	19°	25"	2200 lbs	112 Gal.	X	240
228 Cuddy	22'-7"	8'- 0"	13"	19°	25"	2300 lbs	123 Gal.	X	240
235	23'-0"	8'- 0"	12"	19°	25"/30"	2500 lbs	122 Gal.	X	250
236 Inboard	23'-0"	8'- 0"	24"	16°	Full	3800 lbs	80 Gal.	X	260
238 WalkAround	23'-0"	8'- 6"	14"	X	25"	2500 lbs	121 Gal.	X	250
254	25'-7"	8'- 0"	14"	23°	25"/30"	2800 lbs	151 Gal.	X	370
258 Cuddy	25'-7"	8'- 0"	18"	23°	25"/30"	3200 lbs	151 Gal.	X	370
284	28'-5"	9'-10"	24"	X	25"T	6000 lbs	300 Gal.	X	600
286	28'-5"	9'- 10"	30"	13°	Full	8000 lbs	230 Gal.	X	X

<b>1985</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
171 Standard	17'- 0"	7'- 2"	7"	12 °	20"	1400 lbs	35 Gal.	X	135
171 Angler	17'-0"	7'-2"	7"	12 °	20"	1200 lbs	35 Gal.	X	135
20C	20'-0"	8'-0"	9"	19 °	20"	1775 lbs	60 Gal.	X	200
21B	21'-7"	8'- 0"	12"	19 °	25"	2100 lbs	86 Gal.	X	235
224	22'-7"	8'- 0"	14"	19 °	25"	2200 lbs	112 Gal.	X	240
228 Cuddy	22'-7"	8'- 0"	13"	19 °	25"	2300 lbs	123 Gal.	X	240
235	23'-0"	8'- 0"	12"	19 °	25"/30"	2500 lbs	122 Gal.	X	250
236 Inboard	23'-0"	8'- 0"	24"	16 °	Full	3800 lbs	80 Gal.	X	260
238 WalkAround	23'-0"	8'- 6"	14"	X	25"	2500 lbs	121 Gal.	X	250
254	25'-7"	8'- 0"	14"	23 °	25"/30"	2800 lbs	151 Gal.	X	370
258 Cuddy	25'-7"	8'- 0"	18"	23 °	25"/30"	3200 lbs	151 Gal.	X	370
284	28'-5"	9'-10"	24"	X	25"T	6000 lbs	300 Gal.	X	600
286	28'-5"	9'- 10"	30"	13 °	Full	8000 lbs	230 Gal.	X	X

<b>1986</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
171 Standard	17'- 0"	7'- 2"	7"	12°	20"	1400 lbs	35 Gal.	X	135
171 Angler	17'-0"	7'-2"	7"	12°	20"	1200 lbs	35 Gal.	X	135
20C	20'-0"	8'-0"	9"	19°	20"	1775 lbs	60 Gal.	X	200
21B	21'-7"	8'- 0"	12"	19°	25"	2100 lbs	86 Gal.	X	235
224	22'-7"	8'- 0"	14"	19°	25"	2200 lbs	112 Gal.	X	240

228 Cuddy	22'-7"	8'- 0"	13"	19°	25"	2300 lbs	123 Gal.	X	240
231	23'-2"	8'- 0"	12"	19°	25"/30"	2880 lbs	160 Gal.	X	250
236 Inboard	23'-0"	8'- 0"	24"	16°	Full	3800 lbs	80 Gal.	X	260
248 WalkAround	24'-7"	8'- 6"	12"	X	25"/28.5"	3000 lbs	150 Gal.	X	280
254	25'-7"	8'- 0"	14"	23°	25"/30"	2800 lbs	151 Gal.	X	370
258 Cuddy	25'-7"	8'- 0"	18"	23°	25"/30"	3200 lbs	151 Gal.	X	370
261	26'-4"	8'-6"	16"	23°	25"/30"	3600 lbs	200 Gal.	X	400
284/285	28'-5"	9'- 10"	24"	X	25"T	6000 lbs	300 Gal.	X	600
286	28'-5"	9'-10"	30"	13°	Full	8000 lbs	230 Gal.	X	X

<b>1987</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
172 Standard	17'- 0"	7'- 2"	7"	12°	20"	1400 lbs	35 Gal.	X	135
171 Angler	17'-0"	7'-2"	7"	12°	20"	1200 lbs	35 Gal.	X	135
20C	20'-0"	8'-0"	9"	19°	20"	1775 lbs	60 Gal.	X	200
21B	21'-7"	8'- 0"	12"	19°	25"	2100 lbs	86 Gal.	X	235
224	22'-7"	8'- 0"	14"	19°	25"	2200 lbs	112 Gal.	X	240
228 Cuddy	22'-7"	8'- 0"	13"	19°	25"	2300 lbs	123 Gal.	X	240
231	23'-2"	8'- 0"	12"	19°	25"/30"	2880 lbs	160 Gal.	X	250
236 Inboard	23'-0"	8'- 0"	24"	16°	Full	3800 lbs	80 Gal.	X	260
248 WalkAround	24'-7"	8'- 6"	12"	X	25"/28.5"	3000 lbs	150 Gal.	X	280
254	25'-7"	8'- 0"	14"	23°	25"/30"	2800 lbs	151 Gal.	X	370
258 Cuddy	25'-7"	8'- 0"	18"	23°	25"/30"	3200 lbs	151 Gal.	X	370
261	26'-4"	8'-6"	16"	23°	25"/30"	3600 lbs	200 Gal.	X	400
284/285	28'-5"	9'- 10"	24"	X	25"T	6000 lbs	300 Gal.	X	600
286	28'-5"	9'-10"	30"	13°	Full	8000 lbs	230 Gal.	X	X

<b>1988</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
172 Standard	17'- 0"	7'- 2"	7"	12°	20"	1400 lbs	35 Gal.	X	135
171 Angler	17'-0"	7'-2"	7"	12°	20"	1200 lbs	35 Gal.	X	135
20C	20'-0"	8'-0"	9"	19°	20"	1775 lbs	60 Gal.	X	200
21B	21'-7"	8'- 0"	12"	19°	25"	2100 lbs	86 Gal.	X	235
224	22'-7"	8'- 0"	14"	19°	25"	2200 lbs	112 Gal.	X	240
228 Cuddy	22'-7"	8'- 0"	13"	19°	25"	2300 lbs	123 Gal.	X	240
231	23'-2"	8'- 0"	12"	19°	25"/30"	2880 lbs	160 Gal.	X	250
236 Inboard	23'-0"	8'- 0"	24"	16°	Full	3800 lbs	80 Gal.	X	260

248 WalkAround	24'-7"	8'- 6"	12"	X	25"/28.5"	3000 lbs	150 Gal.	X	280
254	25'-7"	8'- 0"	14"	23°	25"/30"	2800 lbs	151 Gal.	X	370
258 Cuddy	25'-7"	8'- 0"	18"	23°	25"/30"	3200 lbs	151 Gal.	X	370
261	26'-4"	8'-6"	16"	23°	25"/30"	3600 lbs	200 Gal.	X	400
284/285	28'-5"	9'- 10"	24"	X	25"T	6000 lbs	300 Gal.	X	600
286	28'-5"	9'-10"	30"	13°	Full	8000 lbs	230 Gal.	X	X
<b>1989</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
171 Classic	17'- 0"	7'- 2"	7"	12°	20"	1400 lbs	35 Gal.	X	135
171 Angler	17'-0"	7'-2"	7"	12°	20"	1200 lbs	35 Gal.	X	135
191 Classic	19'-0"	8'-0"	9"	19°	25"	1900 lbs	60 Gal.	X	150
201	20'-3"	8'- 0"	9"	19°	25"	2150 lbs	60 Gal.	X	200
210 Walk Arounc	21'-3"	8'- 0"	13"	20°	25"	2500 lbs	110 Gal.	X	230
211	21'-8"	8'- 0"	13"	19°	25"	2400 lbs	86 Gal.	X	235
220 Cuddy	22'-7"	8'- 0"	13"	19°	25"	2500 lbs	110 Gal.	X	240
221	22'-8"	8'- 0"	13"	19°	25"	2480 lbs	110 Gal.	X	250
230 WalkAround	23'-0"	8'- 0"	14"	17°	20"/25"	2800 lbs	120 Gal.	X	250
231	23'-2"	8'- 0"	13"	19°	25"/30"	2880 lbs	150 Gal.	X	250
236 Inboard	23'-0"	8'- 0"	24"	16°	Full	3800 lbs	80 Gal.	X	260
240 Walk Arounc	24'-6"	8'-6"	14"	23°	Full	3600 lbs	150 Gal.	X	280
241	24'-4"	8'- 6"	16"	23°	25"/30"	3400 lbs	180 Gal.	X	400
250 Cuddy	25'-7"	8'-0"	18"	23°	25"/30"	3200 lbs	151 Gal.	X	370
251	25'-7"	8'- 0"	14"	23°	25"/30"	3200 lbs	151 Gal.	X	370
260	26'-0"	8'-6"	14"	23°	30"	4750 lbs	200 Gal.	X	400
261	26'-0"	8'- 6"	16"	23°	25"/30"	3600 lbs	200 Gal.	X	400
281/285	28'-5"	9'-10"	24"	X	30"	6000 lbs	300 Gal.	X	600
286	28'-5"	9'- 10"	30"	13°	Full	8000 lbs	230 Gal.	X	X
<b>1990</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
171 Classic	17'- 0"	7'- 2"	7"	12°	20"	1400 lbs	35 Gal.	X	135
171 Angler	17'-0"	7'-2"	7"	12°	20"	1200 lbs	35 Gal.	X	135
191 Classic	19'-0"	8'-0"	9"	12°	25"	1900 lbs	60 Gal.	X	150
201	20'-3"	8'- 0"	9"	19°	25"	2150 lbs	60 Gal.	X	200
210 Walk Arounc	21'-3"	8'- 0"	13"	20°	25"	2500 lbs	110 Gal.	X	230
211	21'-8"	8'- 0"	13"	19°	25"	2400 lbs	86 Gal.	X	235



221	22'-8"	8'- 0"	13"	19°	25"	2480 lbs	110 Gal.	X	250
230 WalkAround	23'-0"	8'- 0"	13"	17°	20"/25"	2800 lbs	120 Gal.	X	250
230B WalkAroun	23'-0"	8'- 0"	14"	17°	Full	2800 lbs	120 Gal.	X	250
231	23'-2"	8'- 0"	13"	19°	25"/30"	2880 lbs	150 Gal.	X	250
236 Inboard	23'-0"	8'- 0"	24"	16°	Full	6800 lbs	80 Gal.	X	260
241	24'-4"	8'-6"	16"	23°	25"/30"	3400 lbs	180 Gal.	X	400
250 WalkAround	25'-4"	8'- 6"	18"	23°	30"	3500 lbs	151 Gal.	X	400
250B WalkAroun	25'-4"	8'-6"	18"	23°	Full	3500 lbs	151 Gal.	25 Gal.	400
251	25'-7"	8'- 0"	14"	23°	25"/30"	3200 lbs	151 Gal.	X	370
260	26'-0"	8'-6"	14"	23°	30"	4750 lbs	200 Gal.	X	400
260B	26'-0"	8'- 6"	14"	23°	Full	4750 lbs	200 Gal.	25 Gal.	400
261	26'-0"	8'-6"	16"	23°	25"/30"	3600 lbs	200 Gal.	X	400
281/285	28'-5"	9'- 10"	24"	X	30"	6000 lbs	300 Gal.	X	600
286	28'-5"	9'-10"	30"	13°	Full	8000 lbs	230 Gal.	20 Gal.	X

<b>1991</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
171 Classic	17'- 3"	7'- 2"	7"	12°	20"	1250 lbs	35 Gal.	X	135
171 Angler	17'-3"	7'-2"	7"	12°	20"/25"	1250 lbs	35 Gal.	X	135
191 Classic	19'-0"	8'-0"	9"	12°	25"	1900 lbs	60 Gal.	X	150
201	20'-3"	8'- 0"	9"	19°	25"	2150 lbs	60 Gal.	X	200
210 Walk Arounc	21'-3"	8'- 0"	13"	20°	25"	2620 lbs	110 Gal.	X	230
211	21'-8"	8'- 0"	13"	19°	25"	2400 lbs	86 Gal.	X	235
221	22'-8"	8'- 0"	13"	19°	25"	2480 lbs	110 Gal.	X	250
230 WalkAround	23'-0"	8'- 0"	14"	17°	20"/25"	2800 lbs	120 Gal.	X	250
230B WalkAroun	23'-0"	8'- 0"	14"	17°	Full	2800 lbs	120 Gal.	X	250
231	23'-2"	8'- 0"	13"	19°	25"/30"	2880 lbs	150 Gal.	X	250
236 Inboard	23'-0"	8'- 0"	24"	16°	Full	6800 lbs	80 Gal.	X	260
241	24'-4"	8'-6"	16"	23°	25"/30"	3400 lbs	180 Gal.	X	400
250 WalkAround	25'-4"	8'- 6"	18"	23°	30"	3500 lbs	151 Gal.	X	400
250B WalkAroun	25'-4"	8'-6"	18"	23°	Full	3500 lbs	151 Gal.	25 Gal.	400
251	25'-7"	8'- 0"	14"	23°	25"/30"	3200 lbs	151 Gal.	X	370
260	26'-0"	8'-6"	14"	23°	30"	4750 lbs	200 Gal.	25 Gal.	400
260B	26'-0"	8'- 6"	14"	23°	Full	4750 lbs	200 Gal.	25 Gal.	400
261	26'-0"	8'-6"	16"	23°	25"/30"	3600 lbs	200 Gal.	X	400
261B	26'-4"	8'- 6"	16"	23°	Full	3900 lbs	200 Gal.	X	400

281/285	28'-5"	9'-10"	24"	X	30"	6000 lbs	300 Gal.	X	600
286	28'-5"	9'- 10"	30"	13°	Full	8000 lbs	230 Gal.	20 Gal.	X
<b>1992</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
171 Classic	17'- 3"	7'- 2"	9"	12°	20"	1250 lbs	35 Gal.	X	135
171 Angler	17'-3"	7'-2"	9"	12°	20"/25"	1250 lbs	35 Gal.	X	135
181 Flats	17'-10"	8'-0"	7"	12°	20"	995 lbs	50 Gal.	X	150
191 Classic	19'-0"	8'- 0"	9"	12°	25"	1900 lbs	60 Gal.	X	150
201	20'-3"	8'- 0"	9"	19°	25"	2150 lbs	60 Gal.	X	200
210 WalkAround	21'-9"	8'- 0"	13"	20°	25"	2700 lbs	98 Gal.	X	230
211 Classic	21'-10"	8'- 0"	13"	19°	25"	2200 lbs	110 Gal.	X	250
215 Dual	21'-10"	8'- 0"	13"	19°	25"	2300 lbs	110 Gal.	X	250
221	22'-8"	8'- 0"	13"	19°	25"/30"	2600 lbs	150 Gal.	X	280
221B	22'-8"	8'- 0"	13"	19°	Full	2600 lbs	150 Gal.	X	280
230 WalkAround	23'-0"	8'- 0"	14"	17°	25"	3100 lbs	120 Gal.	X	250
230B WalkAroun	23'-0"	8'-0"	14"	17°	Full	3100 lbs	120 Gal.	X	260
236 Inboard	23'-0"	8'- 0"	24"	16°	Full	3800 lbs	80 Gal.	X	260
241	24'-4"	8'-6"	16"	23°	25"/30"	3800 lbs	185 Gal.	X	400
250 WalkAround	25'-8"	8'- 6"	18"	23°	30"	4000 lbs	181 Gal.	X	400
250B WalkAroun	25'-8"	8'-6"	18"	23°	Full	4000 lbs	181 Gal.	25 Gal.	400
251	25'-7"	8'- 0"	14"	23°	25"/30"	3400 lbs	151 Gal.	X	370
261	26'-0"	8'-6"	16"	23°	25"/30"	3900 lbs	200 Gal.	X	400
261B	26'-4"	8'- 6"	16"	23°	Full	3900 lbs	200 Gal.	X	400
270B WalkAroun	27'-8"	8'-6"	17.5"	23°	Full	4750 lbs	200 Gal.	25 Gal.	400
286	28'-5"	9'- 10"	30"	13°	Full	8000 lbs	213 Gal.	20 Gal.	X
<b>1993</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
151 Flats	15'- 5"	6'- 6"	6"	12°	20"	700 lbs	25 Gal.	X	90
161 Flats	16'-9"	7'-3"	6"	12°	20"	850 lbs	35 Gal.	X	130
171 Classic	17'- 3"	7'- 2"	9"	12°	20"	1250 lbs	35 Gal.	X	135
171 Angler	17'-3"	7'-2"	9"	12°	20"/25"	1250 lbs	35 Gal.	X	135
181 Flats	17'-10"	8'-0"	7"	12°	20"	995 lbs	50 Gal.	X	150
191 Classic	19'-0"	8'- 0"	9"	12°	25"	1900 lbs	60 Gal.	X	150
211 Classic	21'-10"	8'- 0"	13"	19°	25"	2200 lbs	110 Gal.	X	250
213 Classic	21'-9"	8'- 0"	13"	20°	25"	2700 lbs	98 Gal.	X	230

215 Dual	21'-10"	8'- 0"	13"	19°	25"	2400 lbs	110 Gal.	X	250
221	22'-8"	8'- 0"	13"	19°	25"/30"	2600 lbs	150 Gal.	X	280
221B	22'-8"	8'- 0"	13"	19°	Full	2600 lbs	150 Gal.	X	250
233 WalkAround	24'-9"	8'- 6"	16"	23°	Full	3800 lbs	165 Gal.	25 Gal.	350
236 Inboard	23'-0"	8'- 0"	24"	16°	Full	3800 lbs	80 Gal.	X	260
241	24'-4"	8'-6"	16"	23°	25"/30"	3800 lbs	185 Gal.	X	400
251	25'-7"	8'- 0"	14"	23°	25"/30"	3400 lbs	151 Gal.	X	370
253B	25'-8"	8'-6"	16"	23°	Full	4000 lbs	181 Gal.	25 Gal.	400
261	26'-0"	8'- 6"	16"	23°	25"/30"	3900 lbs	200 Gal.	X	400
261B	26'-4"	8'-6"	16"	23°	Full	3900 lbs	200 Gal.	X	400
263 WalkAround	28'-7"	9'- 6"	19"	23°	Full	5000 lbs	240 Gal.	40 Gal.	550
273B WalkAroun	27'-8"	8'-6"	17.5"	23°	Full	4750 lbs	200 Gal.	25 Gal.	400
286	28'-5"	9'- 10"	30"	13°	Full	8000 lbs	230 Gal.	20 Gal.	X
290 Sportsfish	28'-3"	10'-0"	23"	13°	Full	7500 lbs	300 Gal.	40 Gal.	600
295 Sportfish	31'-3"	10'- 0"	21"	13°	Full	6800 lbs	300 Gal.	40 Gal.	600

<b>1994</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
161 Flats	16'-9"	7'-3"	6"	12°	20"	850 lbs	35 Gal.	X	130
171 Classic	17'- 3"	7'- 2"	9"	12°	20"	1250 lbs	35 Gal.	X	135
171 Angler	17'-3"	7'-2"	9"	12°	20"/25"	1250 lbs	35 Gal.	X	135
181 Flats	17'-10"	8'-0"	7"	12°	20"	995 lbs	50 Gal.	X	150
191 Classic	19'-0"	8'- 0"	9"	12°	25"	1900 lbs	60 Gal.	X	150
195 Dual	19'-10"	8'- 0"	13"	19°	25"	2000 lbs	86 Gal.	X	200
201	20'-4"	8'- 0"	11"	19°	25"	2150 lbs	100 Gal.	X	200
211 Classic	21'-10"	8'- 0"	13"	19°	25"	2200 lbs	110 Gal.	X	250
213 Classic	21'-9"	8'- 0"	13"	20°	Full	2700 lbs	98 Gal.	X	230
215 Dual	21'-10"	8'- 0"	13"	19°	25"	2400 lbs	110 Gal.	X	250
221	22'-8"	8'- 0"	13"	19°	25"/30"	2600 lbs	150 Gal.	X	280
221B	22'-8"	8'- 0"	13"	19°	Full	2600 lbs	150 Gal.	X	250
233 WalkAround	24'-9"	8'- 6"	16"	23°	Full	3800 lbs	165 Gal.	25 Gal.	350
236 Inboard	23'-0"	8'- 0"	24"	16°	Full	3800 lbs	80 Gal.	X	260
241	24'-4"	8'-6"	16"	23°	25"/30"	3800 lbs	185 Gal.	X	400
241B	26'-2"	8'- 6"	16"	23°	Full	3800 lbs	150 Gal.	X	400
243 WalkAround	26'-2"	8'-6"	16"	23°	Full	4000 lbs	190 Gal.	25 Gal.	400
251	25'-4"	8'- 0"	14"	23°	25"/30"	3400 lbs	151 Gal.	X	370

261	26'-0"	8'-6"	16"	23°	30"	3900 lbs	200 Gal.	X	400
261B	28'-1"	8'- 6"	16"	23°	Full	4100 lbs	185 Gal.	X	450
263 WalkAround	28'-7"	9'-6"	19"	23°	Full	5000 lbs	240 Gal.	40 Gal.	550
286	28'-5"	9'- 10"	30"	13°	Full	8000 lbs	230 Gal.	20 Gal.	X
290 Sportsfish	28'-3"	10'-0"	23"	13°	Full	7500 lbs	300 Gal.	40 Gal.	600
295 Sportfish	31'-3"	10'- 0"	21"	13°	Full	6800 lbs	300 Gal.	40 Gal.	600

<b>1995</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
17	17'-3"	7'-2"	9"	12°	20"	1250 lbs	35 Gal.	X	135
171 Flats	16'- 9"	7'- 3"	6"	12°	20"	850 lbs	35 Gal.	X	130
171 Angler	17'-0"	7'-0"	9"	12°	20"/25"	1250 lbs	45 Gal.	X	125
181 Flats	17'-10"	8'-0"	7"	12°	20"	995 lbs	50 Gal.	X	150
19	19'-0"	8'- 0"	9"	12°	25"	1900 lbs	60 Gal.	X	150
201	20'-4"	8'- 0"	11"	19°	25"	2150 lbs	100 Gal.	X	200
205 Dual	19'-10"	8'- 0"	13"	19°	25"	2000 lbs	86 Gal.	X	200
22	21'-10"	8'- 0"	13"	19°	25"	2200 lbs	110 Gal.	X	250
223 WalkAround	21'-9"	8'- 0"	13"	20°	Full	2700 lbs	98 Gal.	X	230
225 Dual	21'-10"	8'- 0"	13"	19°	25"	2400 lbs	110 Gal.	X	250
231	22'-8"	8'- 0"	13"	19°	25"/30"	2600 lbs	150 Gal.	X	280
232	22'-8"	8'- 0"	13"	19°	Full	2600 lbs	150 Gal.	X	250
236 Inboard	23'-0"	8'- 0"	24"	16°	Full	3800 lbs	80 Gal.	X	260
241	24'-4"	8'- 6"	16"	23°	25"/30"	3800 lbs	185 Gal.	X	400
243 WalkAround	23'-11"	8'-6"	14"	23°	Full	3000 lbs	125 Gal.	X	300
251	25'-4"	8'- 0"	14"	23°	25"/30"	3400 lbs	151 Gal.	X	370
261	26'-0"	8'-6"	16"	23°	30"	3900 lbs	200 Gal.	X	400
251	25'-4"	8'- 0"	14"	23°	25"/30"	3400 lbs	151 Gal.	X	370
261	26'-0"	8'-6"	16"	23°	30"	3900 lbs	200 Gal.	X	400
262	26'-2"	8'- 6"	16"	23°	Full	3800 lbs	150 Gal.	X	400
263 WalkAround	26'-2"	8'-6"	16"	23°	Full	4000 lbs	190 Gal.	25 Gal.	400
282	28'-1"	8'- 6"	16"	23°	Full	4100 lbs	185 Gal.	X	450
286	28'-5"	9'-10"	30"	13°	Full	8000 lbs	230 Gal.	20 Gal.	X
293 WalkAround	28'-7"	9'- 6"	19"	23°	Full	5000 lbs	240 Gal.	40 Gal.	550
295 Sportfish	31'-3"	10'-0"	21"	13°	Full	6800 lbs	300 Gal.	40 Gal.	600

<b>1996</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
-------------	-------------------	------	------------	---------------------	----------------	---------------	---------------	----------------------	--------

17	17'-3"	7'-2"	9"	12°	20"/25"	1250 lbs	35 Gal.	X	135
171 Flats	16'- 9"	7'- 3"	6"	12°	20"	850 lbs	35 Gal.	X	130
181 Flats	17'-0"	8'-0"	7"	12°	20"	995 lbs	50 Gal.	X	150
19	19'-0"	8'-0"	9"	12°	25"	1900 lbs	60 Gal.	X	150
201	20'-4"	8'- 0"	11"	19°	25"	2150 lbs	100 Gal.	X	200
205 Dual	19'-10"	8'- 0"	13"	19°	25"	2000 lbs	86 Gal.	X	200
223 WalkAround	21'-9"	8'- 0"	13"	20°	25"	2700 lbs	98 Gal.	X	230
225 Dual	21'-10"	8'- 0"	13"	19°	25"	2400 lbs	110 Gal.	X	250
231	22'-8"	8'- 0"	13"	19°	25"/30"	2600 lbs	150 Gal.	X	280
232	22'-8"	8'- 0"	13"	19°	Full	2600 lbs	150 Gal.	X	250
243 WalkAround	23'-11"	8'- 6"	14"	23°	25"	3000 lbs	125 Gal.	X	300
251	25'-4"	8'- 0"	14"	23°	25"/30"	3400 lbs	151 Gal.	X	370
262	26'-2"	8'- 6"	16"	23°	25"/30"	3800 lbs	150 Gal.	X	400
263 WalkAround	26'-2"	8'- 6"	16"	23°	25"/30"	4000 lbs	190 Gal.	X	400
282	28'-1"	8'-6"	16"	23°	25"	4100 lbs	235/50 Gal.	X	450
293 WalkAround	28'-7"	9'- 6"	19"	23°	25"	5000 lbs	240 Gal.	40 Gal.	550
295 CC/Dual	31'-3"	10'-0"	21"	13°	25"	6800 lbs	300 Gal.	40 Gal.	600

<b>1997</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
171	17'-3"	7'-2"	9"	12°	20"	1250 lbs	35 Gal.	X	135
171 LT	16'- 9"	7'- 3"	6"	12°	20"	850 lbs	35 Gal.	X	130
181 LT	17'-10"	8'-0"	7"	12°	20"	995 lbs	50 Gal.	X	150
191	19'-4"	8'-2"	12"	17°	25"	1900 lbs	70 Gal.	X	150
221	21'-10"	8'- 2"	13"	20°	25"	2600 lbs	120 Gal.	X	250
223 WalkAround	21'-9"	8'- 0"	13"	20°	25"	2700 lbs	98 Gal.	X	230
231	22'-8"	8'- 0"	13"	19°	25"/30"	2600 lbs	150 Gal.	X	280
232	22'-8"	8'- 0"	13"	19°	Full	2600 lbs	150 Gal.	X	250
243 WalkAround	24'-9"	8'- 6"	16"	23°	25"/30"	4000 lbs	130 Gal.	25 Gal.	400
252	24'-9"	8'- 6"	14"	23°	25"/30"	4000 lbs	200 Gal.	X	300
263 WalkAround	26'-2"	8'- 6"	16"	23°	25"/30"	4500 lbs	190 Gal.	25 Gal.	400
282	28'-1"	8'- 6"	16"	23°	25"	4500 lbs	235 Gal.	X	450
293 WalkAround	28'-7"	9'-6"	19"	23°	25"	5000 lbs	240 Gal.	40 Gal.	550
295 Dual	28'-3"	10'-0"	21"	13°	25"	6800 lbs	300 Gal.	40 Gal.	600
333 Attack	33'-9"	10'-6"	21"	24.5°	25"/30"	11,500 lbs	350 Gal.	40 Gal.	750

<b>1998</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
171	17'-3"	7'-2"	9"	12°	20"	1250 lbs	35 Gal.	X	135
191	19'-4"	8'-2"	12"	17°	25"	1900 lbs	70 Gal.	X	150
221	21'-10"	8'- 2"	13"	20°	25"	2600 lbs	120 Gal.	X	250
223 WalkAround	21'-9"	8'- 2"	13"	20°	25"	2700 lbs	98 Gal.	X	230
232	22'-8"	8'- 0"	13"	19°	Full	3000 lbs	150 Gal.	X	250
252	24'-9"	8'-6"	14"	23°	25"/30"	4000 lbs	200 Gal.	opt.9 Gall0ns	300
253 WalkAround	24'-9"	8'- 6"	19"	23°	25"/30"	4000 lbs	130 Gal.	25 Gal.	400
282	28'-1"	8'- 6"	16"	23°	25"	4500 lbs	235 Gal.	opt.9 Gall0ns	450
293 WalkAround	28'-7"	9'- 6"	19"	23°	25"	6000 lbs	240 Gal.	40 Gal.	550
295 Dual	28'-3"	10'-0"	21"	13°	25"	7000 lbs	300 Gal.	40 Gal.	600
333 Attack	33'-9"	10'-6"	21"	24.5°	25"/30"	11,500 lbs	350 Gal.	40 Gal.	750
<b>1999</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
171	17'-3"	7'-2"	9"	12°	20"	1250 lbs	35 Gal.	X	135
191	19'-4"	8'-2"	12"	17°	25"	1900 lbs	70 Gal.	X	150
192	19'-4"	8'- 6"	12"	16°	25"	1950 lbs	80 Gal.	X	150
195	19'-4"	8'- 6"	12"	16°	25"	2050 lbs	80 Gal.	opt.9 Gall0ns	150
BayShark 2100	21'-10"	8'- 4"	14"	17°	25"	2100 lbs	78 Gal.	X	225
221	21'-10"	8'-2"	14"	20°	25"	2600 lbs	120 Gal.	X	250
232	22'-9"	8'- 6"	14"	20°	25"/30"	3150 lbs	150 Gal.	opt.9 Gal.	300
233 WalkAround	22'-9"	8'- 6"	14"	20°	25"/30"	3400 lbs	145 Gal.	13 Gal.	300
252	24'-9"	8'- 6"	14"	23°	25"/30"	4000 lbs	190 Gal.	opt. 9 Gal.	400
253 WalkAround	24'-9"	8'-6 "	14"	23°	25"/30"	4000 lbs	130 Gal.	25 Gal.	400
282	28'-1"	8'-6"	16"	23°	25"	4500 lbs	235 Gal.	opt.9 Gal.	450
293 WalkAround	28'-7"	9'-6 "	19"	23°	25"	6100 lbs	240 Gal.	40 Gal.	450
333 Attack	33'-9"	10'-6"	21"	24.5°	25"/30"	11,500 lbs	350 Gal.	40 Gal.	750
<b>2000</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
171	17'-3"	7'-2"	9"	12°	20"	1250 lbs	35 Gal.		135
191	19'-4"	8'-2"	12"	17°	25"	1900 lbs	70 Gal.		150
192	19'-4"	8'- 6"	12"	16°	25"	1950 lbs	80 Gal.		150
195	19'-4"	8'- 6"	12"	16°	25"	2050 lbs	80 Gal.	opt.9 Gall0ns	150
BayShark 2100	21'-10"	8'- 4"	14"	17°	25"	2100 lbs	78 Gal.		225

221	21'-10"	8'-2"	14"	20°	25"	2600 lbs	120 Gal.		250
232	22'-9"	8'- 6"	14"	20°	25"/30"	3150 lbs	150 Gal.	opt.9 Gal.	300
233 WalkAround	22'-9"	8'- 6"	14"	20°	25"/30"	3400 lbs	145 Gal.	13 Gal.	300
252	24'-9"	8'- 6"	14"	23°	25"/30"	4000 lbs	190 Gal.	opt. 9 Gal.	400
253 WalkAround	24'-9"	8'-6 "	14"	23°	25"/30"	4000 lbs	130 Gal.	25 Gal.	400
282	28'-1"	8'-6"	16"	23°	25"	4500 lbs	235 Gal.	opt.9 Gal.	450

<b>2001</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
171	17'-3"	7'-2"	9"	12°	20"	1250 lbs	35 Gal.		135
191	19'-4"	8'-2"	12"	17°	25"	1900 lbs	70 Gal.		150
192	19'-4"	8'- 6"	12"	16°	25"	1950 lbs	80 Gal.		150
195	19'-4"	8'- 6"	12"	16°	25"	2050 lbs	80 Gal.	opt.9 Gall0ns	150
BayShark 2100	21'-10"	8'- 4"	14"	17°	25"	2100 lbs	78 Gal.		225
221	21'-10"	8'-2"	14"	20°	25"	2600 lbs	120 Gal.		250
232	22'-9"	8'- 6"	14"	20°	25"/30"	3150 lbs	150 Gal.	opt.9 Gal.	300
233 WalkAround	22'-9"	8'- 6"	14"	20°	25"/30"	3400 lbs	145 Gal.	13 Gal.	300
252	24'-9"	8'- 6"	14"	23°	25"/30"	4000 lbs	190 Gal.	opt. 9 Gal.	400
253 WalkAround	24'-9"	8'-6 "	14"	23°	25"/30"	4000 lbs	130 Gal.	25 Gal.	400
282	28'-1"	8'-6"	16"	23°	25"	4500 lbs	235 Gal.	opt.9 Gal.	450
293 WalkAround	28'-7"	9'-6 "	19"	23°	25"	6100 lbs	240 Gal.	40 Gal.	450
313	31'2"	10' -6"	23"	21°	35"	8,500 lbs	300 Gal.	40 Gal.	500
314	31'-2"	10'-6"	21"	21°	35"	7,500 lbs	300 Gal.	40 Gal.	500

<b>2002</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
171	17'-3"	7'-2"	9"	12°	20"	1250 lbs	35 Gal.		135
191	19'-4"	8'-2"	12"	17°	25"	1900 lbs	70 Gal.		150
192	19'-4"	8'- 6"	12"	16°	25"	1950 lbs	80 Gal.		150
195	19'-4"	8'- 6"	12"	16°	25"	2050 lbs	80 Gal.	opt.9 Gal.	150
BayShark 2100	21'-10"	8'- 4"	14"	17°	25"	2100 lbs	78 Gal.		225
221	21'-10"	8'-2"	14"	20°	25"	2600 lbs	120 Gal.		250
232	22'-9"	8'- 6"	14"	20°	25"/30"	3150 lbs	150 Gal.	opt.9 Gal.	300
233 WalkAround	22'-9"	8'- 6"	14"	20°	25"/30"	3400 lbs	145 Gal.	13 Gal.	300
252	24'-9"	8'- 6"	14"	23°	25"/30"	4000 lbs	190 Gal.	opt. 9 Gal.	400
253 WalkAround	24'-9"	8'-6 "	14"	23°	25"/30"	4000 lbs	130 Gal.	25 Gal.	400
282	28'-1"	8'-6"	16"	23°	25"	4500 lbs	235 Gal.	opt.9 Gal.	450

293 WalkAround	28'-7"	9'-6 "	19"	23°	25"	6100 lbs	240 Gal.	40 Gal.	450
313	31'2"	10' -6"	23"	21°	35"	8,500 lbs	300 Gal.	40 Gal.	500
314	31'-2"	10'-6"	21"	21°	35"	7,500 lbs	300 Gal.	40 Gal.	500

<b>2003</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
171	17'-3"	7'-2"	9"	12°	X	1250 lbs	40 Gal.	X	135
192	19'-4"	8'-6"	12"	16°	X	1950 lbs	80 Gal.	X	150
195	19'-4"	8'- 6"	12"	16°	X	2100 lbs	80 Gal.	X	150
201	20'-3"	8'-2"	12"	12°	X	2000 lbs	75 Gal.	X	200
221	21'-10"	8'-2"	14"	20°	X	2600 lbs	120 Gal.	X	250
232	22'-9"	8'- 6"	14"	20°	X	3150 lbs	150 Gal.	X	300
252	24'-9"	8'- 6"	14"	23°	X	4000 lbs	209 Gal.	X	400
253 WalkAround	24'-9"	8'-6 "	14"	23°	X	4000 lbs	130 Gal.	X	400
282	28'-1"	8'-6"	16"	23°	X	4500 lbs	235 Gal.	X	450
293 WalkAround	28'-7"	9'-6 "	19"	23°	X	6100 lbs	240 Gal.	X	450
313	31'3"	10'-6"	21"	21°	X	7,500 lbs	300 Gal.	X	500
314	31'-3"	10'-6"	21"	21°	X	7,500 lbs	300 Gal.	X	500

<b>2004</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
171	17'-3"	7'-2"	9"	12°	X	1250 lbs	40 Gal.	X	135
192	19'-4"	8'-6"	12"	16°	X	1950 lbs	80 Gal.	X	150
195	19'-4"	8'- 6"	12"	16°	X	2100 lbs	80 Gal.	X	150
201	20'-3"	8'-2"	12"	12°	X	2000 lbs	75 Gal.	X	200
212 Center Cons	20'-5"	8'-6"	14"	18°	X	2400 lbs	100 Gal.	X	250
232	22'-9"	8'- 6"	14"	20°	X	3150 lbs	150 Gal.	X	300
252	24'-9"	8'- 6"	14"	23°	X	4000 lbs	209 Gal.	X	400
253 WalkAround	24'-9"	8'-6 "	14"	23°	X	4000 lbs	130 Gal.	X	400
314	31'-3"	10'-6"	21"	21°	X	7,500 lbs	300 Gal.	X	500
1901 Inshore	19'-4"	94"	12"	15°	X	1,575 lbs	47 Gal.	X	150
2101 Inshore	21'-4"	194"	12"	15°	X	1,790 lbs	60 Gal.	X	200

<b>2005</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
171	17'-3"	7'-2"	9"	12°	X	1250 lbs	40 Gal.	X	135
192	19'-4"	8'-6"	12"	16°	X	1950 lbs	80 Gal.	X	150
195	19'-4"	8'- 6"	12"	16°	X	2100 lbs	80 Gal.	X	150



201	20'-3"	8'-2"	12"	12°	X	2000 lbs	75 Gal.	X	200
212 Center Cons	20'-5"	8'-6"	14"	18°	X	2400 lbs	100 Gal.	X	250
232	22'-9"	8'- 6"	14"	20°	X	3150 lbs	150 Gal.	X	300
252	24'-9"	8'- 6"	14"	23°	X	4000 lbs	209 Gal.	X	400
253 WalkAround	24'-9"	8'-6 "	14"	23°	X	4000 lbs	130 Gal.	X	400
314	31'-3"	10'-6"	21"	21°	X	7,500 lbs	300 Gal.	X	500
1901 Inshore	19'-4"	94"	12"	15°	X	1,575 lbs	47 Gal.	X	150
2101 Inshore	21'-4"	194"	12"	15°	X	1,790 lbs	60 Gal.	X	200

<b>2006</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
284 CC	28'-4"	9'-10"	21"	21°	30"	6,000 lbs	235 gal.	X	600
264 CC	26'-0"	9'-2"	20"	21°	30"	4,500 lbs	194 gal.	X	450
234 CC	23'-4"	8'-6 "	14"	21°	30"	3,500 lbs	150 gal.	X	300
212 CC	21'-5"	8'-6"	14"	18°	25"	3,100 lbs	93 gal.	X	250
192 CC	19'-4"	8'- 6 "	12"	16°	25"	2,300 lbs	80 gal.	X	150
171 CC	17'-3"	7'-2"	9"	12°	20"	1,500 lbs	37 gal.	X	125
253 WA	27'-7"	8'-6"	14"	23°	30"	4,200 lbs	130 gal.	X	400
215 WA	21'-5"	8'-6"	16"	18°	25"	3,300 lbs	93 gal.	X	250
216 DC	21'-5"	8'- 6"	15"	18°	25"	3,200 lbs	93 gal.	X	250
195 DC	19'-4"	8'-6"	12"	16°	25"	2,600 lbs	80 gal.	X	150
181 Inshore	18'-0"	7'-6"	X	X	25"	990 lbs	35 gal.	X	90
191 Inshore	19'-3"	8'-3"	X	X	25"	1,320 lbs	47 gal.	X	175
211 Inshore	21'-9"	8'-3"	X	X	25"	1,400 lbs	60 gal.	X	225
241 Inshore	23'-11"	8'-6"	X	X	25"	1,400 lbs	96 gal.	X	275
1801 Inshore	17'-8"	7'-1"	X	X	25"	1,190 lbs	35 gal.	X	125
1901 Inshore	19'-1"	7'-8"	X	X	25"	1,575 lbs	47 gal.	X	150
2101 Inshore	21'-5"	7'-9"	X	X	25"	1,790 lbs	60 gal.	X	225
2201 Inshore	21'-5"	7'-9"	X	X	25"	1,890 lbs	60 gal.	X	225

<b>2007</b>	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
284 CC	28'-4"	9'-10"	21"	21°	30"	6,000 lbs	235 gal.	X	600
264 CC	26'-0"	9'-2"	20"	21°	30"	4,500 lbs	194 gal.	X	450
234 CC	23'-4"	8'-6"	18"	21°	30"	3,500 lbs	150 gal.	X	300
212 CC	21'-5"	8'-6"	14"	18°	25"	3,100 lbs	93 gal.	X	250
204 CC	20'-4"	8'-4"	12"	18°	25"	2,000 lbs	85 gal.	X	225

192 CC	19'-4"	8'- 6 "	12"	16°	25"	2,300 lbs	80 gal.	X	150
184 CC	18'-4"	8'-2"	12"	18°	25"	1,800 lbs	56 gal.	X	150
171 CC	17'-3"	7'-2"	9"	12°	20"	1,500 lbs	37 gal.	X	125
314 Cuddy	31'-3"	10'-6"	21"	21°	35"	7,500 lbs	300 gal.	X	600
284 WA	28'-4"	9'-10"	21"	X	30"	X	194 gal.	X	600
264 WA	26'-0"	9'-2"	21"	X	30"	6,500 lbs	174 gal.	X	450
215 WA	21'-5"	8'-6"	16"	18°	25"	3,300 lbs	93 gal.	X	250
216 DC	21'-5"	8'- 6"	16"	18°	25"	3,200 lbs	93 gal.	X	250
181 Inshore	17'-11"	7'-5"	15"	15°	25"	1,300 lbs	35 gal.	X	90
191 Inshore	19'-2"	8'-2"	16"	15°	25"	1,600 lbs	47 gal.	X	175
211 Inshore	21'-8"	8'-2"	16"	15°	25"	1,950 lbs	60 gal.	X	225
241 Inshore	23'-11"	8'-6"	16"	15°	25"	2,500 lbs	96 gal.	X	300
1801 Inshore	17'-7"	7'-1"	16"	15°	25"	1,400 lbs	35 gal.	X	125
1901 Inshore	18'-10"	7'-9"	16"	15°	25"	1,700 lbs	47 gal.	X	150
2101 Inshore	21'-4"	7'-9"	15"	15°	25"	2,000 lbs	60 gal.	X	225
2201 Inshore	21'-3"	7'-9"	16"	15°	25"	2,100 lbs	60 gal.	X	225